



SAFETY DATA SHEET

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

1. Identification

Product identifier

Product name Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Product number ID 19555

Recommended use of the chemical and restrictions on use

Application Use as a fuel

Details of the supplier of the safety data sheet

Supplier Neste US, Inc.
3040 Post Oak Blvd, Suite 1700, Houston, Texas 77056
+1 (713) 407 4400
sds@neste.com (chemical safety)

Emergency telephone number

Emergency telephone +61 2 9186 1132, Chemwatch: International Emergency Response Phone Number

National emergency telephone number +358 800 147 111, +358 9 471 977, Poison Information Centre

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Liq. 4 - H227

Health hazards Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304

Label elements

Hazard symbols



Signal word Danger

Hazard statements H227 Combustible liquid.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements P273 Avoid release to the environment.
P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P260 Do not breathe vapor/ spray.
P301+P310 If swallowed: Immediately call a poison center/ doctor.
P331 Do NOT induce vomiting.
P501 Dispose of contents/ container in accordance with national regulations.

Contains Alkanes, C10-20 -branched and linear, Fuels, diesel, Distillates (Fischer-Tropsch), C8-26 -branched and linear

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Other hazards

Hazards not otherwise classified (HNOC) Risk of soil and ground water contamination. Repeated exposure may cause skin dryness or cracking.

3. Composition/information on ingredients

Mixtures

Alkanes, C10-20 -branched and linear	> 97 %
CAS number: 928771-01-1	

Classification

Flam. Liq. 4 - H227
Asp. Tox. 1 - H304

Fuels, diesel

< 3 %

CAS number: 68334-30-5

Classification

Flam. Liq. 3 - H226
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
Carc. 2 - H351
STOT RE 2 - H373
Asp. Tox. 1 - H304
Not relevant.

Distillates (Fischer-Tropsch), C8-26 - branched and linear

< 2 %

CAS number: 848301-67-7

Classification

Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

Composition comments Mixture of renewable raw material fuel and additives. Contains middle distillate-range iso- and n-paraffinic hydrocarbons. Total aromatics at maximum: 1,0%

4. First-aid measures

Description of first aid measures

Inhalation	Unlikely to be hazardous by inhalation because of the low vapor pressure of the product at ambient temperature. If spray/mist has been inhaled, proceed as follows. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Do not induce vomiting. Get medical attention immediately.
Skin Contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

General information Repeated exposure may cause skin dryness or cracking. Spray/mists may cause respiratory tract irritation. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters

Special hazards arising from the substance or mixture

Specific hazards Combustible liquid. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide (CO).

Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear adequate protective equipment at all operations.

For emergency responders Prevent unauthorized access. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge.

Environmental precautions

Environmental precautions Avoid release to the environment. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Risk of soil and ground water contamination.

Methods and material for containment and cleaning up

Methods for cleaning up Immediately start clean-up of the liquid and contaminated soil. Contain spillage with sand, earth or other suitable non-combustible material. Pay attention to the fire and health hazards caused by the product.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid heat, flames and other sources of ignition. Take precautionary measures against static discharges. Use only outdoors or in a well-ventilated area. Avoid inhalation of vapors and contact with skin and eyes. Use personal protective equipment and/or local ventilation when needed. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Conditions for safe storage, including any incompatibilities

Storage precautions Flammable liquid storage. Store in accordance with local regulations. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Only store in correctly labeled containers. Use containers made of the following materials: Carbon steel. Stainless steel.

Specific end uses(s)

Specific end use(s) Not known.

8. Exposure controls/Personal protection

Ingredient comments The individual limit values can be applied for the hydrocarbons.
Diesel fuel as total hydrocarbons; ACGIH TLV®-TWA (8h) 100 mg/m3 (IFV).

Exposure controls

Appropriate engineering controls Provide adequate ventilation. Use personal protective equipment and/or local ventilation when needed. Handle in accordance with good industrial hygiene and safety practice. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

Eye/face protection Spectacles.

Hand protection Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). The breakthrough time for any glove material may be different for different glove manufacturers. Change protective gloves regularly.

Other skin and body protection Protective clothing when needed. Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Filter must be changed often enough. At high concentrations a breathing apparatus must be used (self-contained or fresh air hose breathing apparatus).

Environmental exposure controls Store in a demarcated bunded area to prevent release to drains and/or watercourses.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Clear.

Odor Mild.

Odor threshold No information available.

pH No information available.

Melting point Pour point < -20°C @ 1013 hPa (BS4633, EC A1)

Initial boiling point and range 180-320°C (EN ISO 3405)

Flash point > 61°C (EN ISO 2719, EC A9)

Upper/lower flammability or explosive limits No information available.

Vapor pressure 0,087 kPa @ 25°C (EC A4)

Vapor density No information available.

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Relative density	0,77 - 0,79 @ 15/4°C (EN ISO 12185, EC A3)
Solubility(ies)	Insoluble in water. ~ 0,075 mg/l water @ 25°C (calculated) Soluble in the following materials: Methanol. Hydrocarbons.
Partition coefficient	log Kow: > 6,5 (EC A8)
Auto-ignition temperature	204°C (EC A15)
Decomposition Temperature	No information available.
Viscosity	Kinematic viscosity 4.0 mm ² /s @ 20°C 2.6 mm ² /s @ 40°C (OECD 114) Dynamic viscosity ≤ 5 mPa s @ 20°C
Explosive properties	Not considered to be explosive. (EC A14)
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Other information	Not known.

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Keep away from heat, sparks and open flame.
Materials to avoid	Oxidizing agents.
Hazardous decomposition products	Does not decompose when used and stored as recommended.

11. Toxicological information

Information on toxicological effects

Toxicological effects Acute toxicity (any route of exposure) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 367.89

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met. (EC B4) Repeated exposure may cause skin dryness or cracking. The product irritates mucous membranes and may cause abdominal discomfort if swallowed. May cause respiratory system irritation.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met. (EC B5)

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met. (EC B6)

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met. (EC B10, B13/14 & B17).

Carcinogenicity

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met. (OECD 416)

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Route of exposure Inhalation Ingestion Skin and/or eye contact

Toxicological information on ingredients.

Alkanes, C10-20 -branched and linear

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat (EC B1 tris)

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat (EC B3)

Fuels, diesel

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat (OECD 401, 420)

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 4300 mg/kg, Dermal, Rabbit (OECD 434)

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ 3,6 - 5,4 mg/l, Inhalation, (4h), Rat (OECD 403)

ATE inhalation (vapours mg/l) 11.0

Distillates (Fischer-Tropsch), C8-26 - branched and linear

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat

12. Ecological information

Acute aquatic toxicity

Summary Based on available data the classification criteria are not met.

Chronic aquatic toxicity

Summary Based on available data the classification criteria are not met.

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Ecological information on ingredients.

Alkanes, C10-20 -branched and linear

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: > 1000 mg/l, Fish WAF (OECD 203)
Acute toxicity - aquatic invertebrates	EL ₅₀ , 48 hours: > 100 mg/l, WAF (OECD 202)
Acute toxicity - aquatic plants	EL ₅₀ , 72 hours: > 100 mg/l, Algae WAF (OECD 201)
Acute toxicity - microorganisms	EC ₅₀ , 30 minutes: > 1000 mg/l, Micro-organisms (wastewater sludge) EC ₅₀ , 3 hours: > 1000 mg/l, Micro-organisms (wastewater sludge) (OECD 209)

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 1 mg/l, LOEC, 21 days: 3,2 mg/l, WAF (OECD 211) NOEC, 10 days: 373 mg/kg, Sediment organisms LOEC, 10 days: 1165 mg/kg, Sediment organisms LC ₅₀ , 10 days: 1200 mg/kg, Sediment organisms (OSPAR Protocols, Part A: Sediment Bioassay, 2005)
---	---

Fuels, diesel

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: 21 mg/l, Oncorhynchus mykiss (Rainbow trout) NOEL, 96 hours: 10 mg/l, Oncorhynchus mykiss (Rainbow trout) WAF (OECD 203, EC C.1)
Acute toxicity - aquatic invertebrates	EL ₅₀ , 48 hours: 68 mg/l, Daphnia magna NOEL, 48 hours: 46 mg/l, Daphnia magna WAF (OECD 202, EC C.2)
Acute toxicity - aquatic plants	EbL ₅₀ , 72 hours: 10 mg/l, Pseudokirchneriella subcapitata NOEL, 72 hours: 1 mg/l, Pseudokirchneriella subcapitata WAF (OECD 201, EC C.3)
Acute toxicity - microorganisms	EL ₅₀ , 40 hours: > 1000 mg/l, Micro-organisms (wastewater sludge) NOEL, 40 hours: 3,22 mg/l, Micro-organisms (wastewater sludge) (QSAR)

Chronic aquatic toxicity

Chronic toxicity - fish early life stage	NOEL, 14 days: 0,08 mg/l, Oncorhynchus mykiss (Rainbow trout) (QSAR)
Chronic toxicity - aquatic invertebrates	NOEL, 21 days: 0,2 mg/l, Daphnia magna (QSAR)

Persistence and degradability

Stability (hydrolysis)	No significant reaction in water.
Biodegradation	Rapidly degradable (OECD 301B).

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Ecological information on ingredients.

Fuels, diesel

Biodegradation	Inherently biodegradable. (OECD 301F)
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	Possibly bioaccumulative.
Partition coefficient	log Kow: > 6,5 (EC A8)
<u>Mobility in soil</u>	
Mobility	Evaporates slowly. The product has poor water-solubility. The product contains substances which are bound to particulate matter and are retained in soil. Log Koc > 5.6 (EC C19).
<u>Other adverse effects</u>	
Other adverse effects	Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Product residues retained in emptied containers can be hazardous. Waste packaging should be collected for reuse or recycling.
-------------------------	--

14. Transport information

Sea transport notes	This cargo is considered an Energy-rich fuel and effective 1 January 2019 should be carried subject to Annex I of MARPOL, see Annex 12 of MEPC.2/Circ.24. Please also refer to MEPC.1/Circ.879 - GUIDELINES FOR THE CARRIAGE OF ENERGY-RICH FUELS AND THEIR BLENDS
<u>UN Number</u>	
UN No. (TDG)	1993
UN No. (IMDG)	Not classified under IMDG.
UN No. (DOT)	1993
<u>UN proper shipping name</u>	
Proper shipping name (TDG)	UN 1993 Flammable Liquid, N.O.S. (Diesel fuel)
Proper shipping name (DOT)	UN 1993 Flammable liquid, N.O.S. (Diesel fuel)
<u>Transport hazard class(es)</u>	
DOT hazard class	3
TDG class	3
<u>Packing group</u>	
TDG Packing Group	III
DOT packing group	III
<u>Environmental hazards</u>	

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Environmentally Hazardous Substance

No.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Bulk (MARPOL 73/78, Annex I): Energy-rich fuels

15. Regulatory information

National regulations

EU regulatory references for the safety data sheet:

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

Inventories

EU - EINECS/ELINCS

Not listed.

Canada - DSL/NDSL

Present.
DSL

US - TSCA

Present.

Australia - AIC

Present.

China - IECSC

Not listed.

16. Other information

Abbreviations and acronyms used in the safety data sheet

ACGIH = American Conference of Governmental Industrial Hygienists
TLV = Treshold Limit Value
TWA = Time-Weighted Average
WAF = Water Accommodated Fraction

Key literature references and sources for data

Regulations, databases, literature, own research. Chemical Safety Report Renewable hydrocarbons (diesel type fraction), 2017.

Revision comments

Updated, sections: 14. NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date

7/26/2022

Supersedes date

11/11/2021

SDS No.

6327

Neste MY Renewable Diesel (R99); Neste Renewable Diesel (R99)

Hazard statements in full	H226 Flammable liquid and vapor. H227 Combustible liquid. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
NFPA - health hazard	0
NFPA - flammability hazard	2
NFPA - instability hazard	0
NFPA - special hazard	-
ACA HMIS Health rating.	2
ACA HMIS Flammability rating.	2
ACA HMIS Physical hazard rating.	0

The information given is based on data currently available to us and is believed to be correct. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for injury or damage from the use of the products described herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.